



## Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

<b>Manufacturer</b>	<b>Superlite Jointings Pvt. Ltd</b>
<b>Address</b>	Jindal Nagar, Village Galand, Dibarsi Road, Hapur, 201015, India
<b>Type</b>	Flange Gasket
<b>Description</b>	Non Asbestos Gasket Materials/ Jointings Sheets,SUPERLITE Asbestos Free Oil 220 (AF Oil 220)
<b>Trade Name</b>	SUPERLITE Asbestos Free Oil 220 (AF Oil 220)
<b>Application</b>	Jointing gasket material for Marine, Offshore & Industrial Piping system
<b>Specified Standard</b>	ASTM
<b>Ratings</b>	<b>Type:</b> AF OIL 220 <b>Max. Operating Temperature:</b> 225° C <b>Max. Operating Pressure:</b> 80 Bar <b>Sheet Thickness:</b> 0.50 mm to 5.00 mm

### TECHNICAL DATA

**Type:** AF OIL 220  
**Density:** 1.6 - 1.9 (g/cm<sup>3</sup>)  
**Tensile Strength:** ≥ 9.50 (N/mm<sup>2</sup>) ASTM F152  
**Compressibility:** 7-17 % ASTM F36  
**Recovery:** ≥ 50.0 % ASTM F36

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

### Mohamed Rila

Team Lead - Environmental Discipline to  
Lloyd's Register EMEA  
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.