



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Superlite Jointings Pvt. Ltd
Address	Jindal Nagar, Village Galand, Dibarsi Road, Hapur, 201015, India
Type	Flange Gasket
Description	Non Asbestos Gasket Materials/ Jointings Sheets,SUPERLITE Asbestos Free Oil 250 (AF Oil 250)
Trade Name	SUPERLITE Asbestos Free Oil 250 (AF Oil 250)
Application	Jointing gasket material for Marine, Offshore & Industrial piping system
Specified Standard	ASTM
Ratings	Type: AF OIL 250 Max. Operating Temperature: 250° C Max. Operating Pressure: 100 Bar Sheet Thickness: 0.50 mm to 5.00 mm

TECHNICAL DATA

Type: AF OIL 250
Density: 1.6 - 1.9 (g/cm³)
Tensile Strength: ≥ 10.50 (N/mm²) ASTM F152
Compressibility: 5-15 % ASTM F36
Recovery: ≥ 50.0 % ASTM F36

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Mohamed Rila

Team Lead - Environmental Discipline to
Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.